

# Dragon 124 - Discs 225 mm 10 h QG-Filt

## Special application

Sanding of wood, paint, filler, car body, PVC



## Supplies as

Discs 225 mm 10 h QG-Filt



Grain	
	<b>WA</b> White aluminiumoxide
<b>X</b>	<b>HA</b> Hardened (Blue fired) Brown aluminiumoxide
	<b>BA</b> Brown aluminiumoxide
	<b>S</b> Silicium carbide
	<b>ZA</b> Zirconia Alumina
	<b>C</b> Ceramic
Topcoat	
	<b>ST</b> Stearate

Grit range																							
P12	P16	P24	P30	P36	P40	P50	P60	P80	P100	P120	P150	P180	P220	P240	P280	P320	P360	P400	P500	P600	P800	P1000	P1200
					<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>(X)</b>	<b>(X)</b>											

Dimension with & without center holes											
125mm	150mm	178mm	203mm	225mm	330mm	375mm	406mm	430mm	450mm	500mm	600mm
				<b>X</b>							

Grain distribution	
	● Close
<b>X</b>	◐ Semi open
	○ Open

Bonding	
	<b>QQ</b> Resin/resin
	<b>SQ</b> Starch/resin
<b>X</b>	<b>BQ</b> Flexible resin/resin
	<b>SS</b> Starch/starch

Back side	
	<b>QG</b> Quick Grip
<b>X</b>	<b>FL</b> Felt

Backing	
	<b>A</b> <80 g/m2 paper
	<b>B</b> 80-100 g/m2 paper
<b>(X)</b>	<b>C</b> 105-125 g/m2 paper
<b>X</b>	<b>D</b> 130-170 g/m2 paper
	<b>E</b> 180-290 g/m2 paper
	<b>F</b> >300 g/m2 paper (reinforced)
	<b>WR</b> 100 -115 g/m2 water resistant
	<b>WL</b> 120 g/m2 light water resistant