

# Dragon 421-(126) Sheets 93 x 230 mm 8 h

## Special application

Sanding of wood, paint, filler, car body, PVC



## Supplies as

Sheets 93 x 230 mm 8 h



| Grain    |           |  |
|----------|-----------|--|
|          | <b>WA</b> | White aluminiumoxide                       |
| <b>X</b> | <b>HA</b> | Hardened (Blue fired) Brown aluminiumoxide |
|          | <b>BA</b> | Brown aluminiumoxide                       |
|          | <b>S</b>  | Silicium carbide                           |
|          | <b>ZA</b> | Zirconia Alumina                           |
|          | <b>C</b>  | Ceramic                                    |
| Topcoat  |           |  |
|          | <b>ST</b> | Stearate                                   |

| Grit range |     |     |     |     |          |     |          |          |          |          |            |            |      |            |      |      |      |      |      |      |      |       |       |
|------------|-----|-----|-----|-----|----------|-----|----------|----------|----------|----------|------------|------------|------|------------|------|------|------|------|------|------|------|-------|-------|
| P12        | P16 | P24 | P30 | P36 | P40      | P50 | P60      | P80      | P100     | P120     | P150       | P180       | P220 | P240       | P280 | P320 | P360 | P400 | P500 | P600 | P800 | P1000 | P1200 |
|            |     |     |     |     | <b>X</b> |     | <b>X</b> | <b>X</b> | <b>X</b> | <b>X</b> | <b>(X)</b> | <b>(X)</b> |      | <b>(X)</b> |      |      |      |      |      |      |      |       |       |

| Dimension with & without center holes |       |       |       |       |       |       |       |       |       |       |       |
|---------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 125mm                                 | 150mm | 178mm | 203mm | 225mm | 330mm | 375mm | 406mm | 430mm | 450mm | 500mm | 600mm |
|                                       |       |       |       |       |       |       |       |       |       |       |       |

| Grain distribution |   |           |
|--------------------|---|-----------|
|                    | ● | Close     |
| <b>X</b>           | ◐ | Semi open |
|                    | ○ | Open      |

| Bonding  |           |                       |
|----------|-----------|-----------------------|
| <b>X</b> | <b>QQ</b> | Resin/resin           |
|          | <b>SQ</b> | Starch/resin          |
|          | <b>BQ</b> | Flexsible resin/resin |
|          | <b>SS</b> | Starch/starch         |

| Back side |           |            |
|-----------|-----------|------------|
| <b>X</b>  | <b>QG</b> | Quick Grip |
|           | <b>FL</b> | Felt       |

| Backing    |  |
|------------|--|
|            | <b>A</b> <80 g/m2 paper                  |
|            | <b>B</b> 80-100 g/m2 paper               |
|            | <b>C</b> 105-125 g/m2 paper              |
| <b>(X)</b> | <b>D</b> 130-170 g/m2 paper              |
| <b>X</b>   | <b>E</b> 180-290 g/m2 paper              |
|            | <b>F</b> >300 g/m2 paper (reinforced)    |
|            | <b>WR</b> 100 -115 g/m2 water resistant  |
|            | <b>WL</b> 120 g/m2 light water resistant |