

## Technical Product Information

### Dragon 124

# Dragon 124 - Rolls 115mm x 2m

## Recommended application

Sanding of wood, paint, filler, car body, PVC



## Variations

Rolls: 2m, 5m, 25m (93mm), 50m



| Grain type |           |                                             |
|------------|-----------|---------------------------------------------|
|            | <b>WA</b> | White aluminium oxide                       |
| <b>X</b>   | <b>HA</b> | Hardened (blue-fired) brown aluminium oxide |
|            | <b>BA</b> | Brown aluminium oxide                       |
|            | <b>S</b>  | Silicium carbide                            |
|            | <b>ZA</b> | Zirconia alumina                            |
|            | <b>C</b>  | Ceramic                                     |
| Topcoat    |           |                                             |
|            | <b>ST</b> | Stearate                                    |

| Grit range |     |     |     |     |     |     |     |     |      |      |      |      |      |      |      |      |      |      |      |      |      |       |       |
|------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|
| P12        | P16 | P24 | P30 | P36 | P40 | P50 | P60 | P80 | P100 | P120 | P150 | P180 | P220 | P240 | P280 | P320 | P360 | P400 | P500 | P600 | P800 | P1000 | P1200 |
|            |     |     |     |     | (X) |     | (X) | (X) | (X)  | (X)  | X    | X    | X    | X    | X    | x    |      |      |      |      |      |       |       |

| Dimension with & without centre holes |       |       |       |       |       |       |       |       |       |       |       |  |
|---------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|
| 125mm                                 | 150mm | 178mm | 203mm | 225mm | 330mm | 375mm | 406mm | 430mm | 450mm | 500mm | 600mm |  |
|                                       |       |       |       |       |       |       |       |       |       |       |       |  |

| Grain distribution |   |           |
|--------------------|---|-----------|
|                    | ● | Close     |
| <b>X</b>           | ◐ | Semi open |
|                    | ○ | Open      |

| Bonding  |           |                      |
|----------|-----------|----------------------|
|          | <b>QQ</b> | Resin/resin          |
|          | <b>SQ</b> | Starch/resin         |
| <b>X</b> | <b>BQ</b> | Flexible resin/resin |
|          | <b>SS</b> | Starch/starch        |

| Back side |           |            |
|-----------|-----------|------------|
|           | <b>QG</b> | Quick Grip |
|           | <b>FL</b> | Felt       |

| Backing    |           |                                            |
|------------|-----------|--------------------------------------------|
|            | <b>A</b>  | <80 g/m <sup>2</sup> paper                 |
|            | <b>B</b>  | 80-100 g/m <sup>2</sup> paper              |
| <b>X</b>   | <b>C</b>  | 120 g/m <sup>2</sup> paper                 |
| <b>(X)</b> | <b>D</b>  | 150 g/m <sup>2</sup> paper                 |
|            | <b>E</b>  | 180-290 g/m <sup>2</sup> paper             |
|            | <b>F</b>  | >300 g/m <sup>2</sup> paper (reinforced)   |
|            | <b>WR</b> | 100 -115 g/m <sup>2</sup> water resistant  |
|            | <b>WL</b> | 120 g/m <sup>2</sup> light water resistant |