

Technical Product Information

Dragon 125 Y

Dragon 125 Y - Rolls 115mm x 50m

Recommended application

Sanding of wood, paint, lacquer, filler



Variations

Rolls: 2m, 5m, 25m, 50m

Also with the height 93mm + 100mm



Grain type		
X	WA	White aluminium oxide
	HA	Hardened (blue-fired) brown aluminium oxide
	BA	Brown aluminium oxide
	S	Silicium carbide
	ZA	Zirconia alumina
	C	Ceramic
Topcoat		
	ST	Stearate

Grit range																							
P12	P16	P24	P30	P36	P40	P50	P60	P80	P100	P120	P150	P180	P220	P240	P280	P320	P360	P400	P500	P600	P800	P1000	P1200
					X		X	X	X	X	X	X		X									

Dimension with & without centre holes												
125mm	150mm	178mm	203mm	225mm	330mm	375mm	406mm	430mm	450mm	500mm	600mm	

Grain distribution		
	●	Close
X	◐	Semi open
	○	Open

Bonding		
X	QQ	Resin/resin
	SQ	Starch/resin
	BQ	Flexible resin/resin
	SS	Starch/starch

Back side		
	QG	Quick Grip
	FL	Felt

Backing		
	A	<80 g/m ² paper
	B	80-100 g/m ² paper
	C	105-125 g/m ² paper
	D	130-170 g/m ² paper
X	E	180-290 g/m ² paper
	F	>300 g/m ² paper (reinforced)
	WR	100 -115 g/m ² water resistant
	WL	120 g/m ² light water resistant