

## Technical product information

### Dragon 421

# Dragon 421 - Rolls 100mm x 50m

## Recommended application


Sanding of wood, paint, filler, car body, PVC



## Variations

Rolls: 5m, 25m, 50m

Also available with height 93 mm and 115mm



| Grain type |    |                                             |
|------------|----|---------------------------------------------|
|            | WA | White aluminium oxide                       |
| X          | HA | Hardened (blue-fired) brown aluminium oxide |
|            | BA | Brown aluminium oxide                       |
|            | S  | Silicium carbide                            |
|            | ZA | Zirconia alumina                            |
|            | C  | Ceramic                                     |
| Topcoat    |    |                                             |
|            | ST | Stearate                                    |

| Grit range |     |     |     |     |     |     |     |     |      |      |      |      |      |      |      |      |      |      |      |      |
|------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|
| P12        | P16 | P24 | P30 | P36 | P40 | P50 | P60 | P80 | P100 | P120 | P150 | P180 | P220 | P240 | P280 | P320 | P360 | P400 | P500 | P600 |
|            |     |     |     |     | X   |     | X   | X   | X    | X    | X    | X    |      | X    |      |      |      |      |      |      |

| Dimension with & without centre holes |       |       |       |       |       |       |       |       |       |       |       |
|---------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 125mm                                 | 150mm | 178mm | 203mm | 225mm | 330mm | 375mm | 406mm | 430mm | 450mm | 500mm | 600mm |
|                                       |       |       |       |       |       |       |       |       |       |       |       |

| Grain distribution |   |           |
|--------------------|---|-----------|
|                    | ● | Close     |
| X                  | ◐ | Semi open |
|                    | ○ | Open      |

| Bonding |    |                      |
|---------|----|----------------------|
| X       | QQ | Resin/resin          |
|         | SQ | Starch/resin         |
|         | BQ | Flexible resin/resin |
|         | SS | Starch/starch        |

| Back side |    |            |
|-----------|----|------------|
|           | QG | Quick Grip |
|           | FL | Felt       |

| Backing |    |                                            |
|---------|----|--------------------------------------------|
|         | A  | <80 g/m <sup>2</sup> paper                 |
|         | B  | 80-100 g/m <sup>2</sup> paper              |
|         | C  | 105-125 g/m <sup>2</sup> paper             |
|         | D  | 130-170 g/m <sup>2</sup> paper             |
| X       | E  | 220 g/m <sup>2</sup> paper                 |
|         | F  | >300 g/m <sup>2</sup> paper (reinforced)   |
|         | WR | 100 -115 g/m <sup>2</sup> water resistant  |
|         | WL | 120 g/m <sup>2</sup> light water resistant |